




FASTSYNC- 320R6 470R6

- Clam shell type laminator for easy maintenance
- Perfect pouch laminator for Photos
- Carrier-free operation



Hot-roller type pouch laminator with innovative Clam shell technology

6 rollers system for high speed lamination

- Designed for hot & cold lamination
- Clam shell design allows easy cleaning and maintenance
- Efficient cooling system supporting the high speed lamination
- The 6 roller assuring the perfect lamination of any type of films
- Precise temperature control by using the internally heated rollers with temperature control which use non-contact infrared sensors

POUCH
LAMINATORS



RoHS



UL-WTDP, CB-TMP Lab.



CE

Pouch Laminators

FASTSYNC pouch laminator series machines are high speed pouch laminators with 6 rollers and make no air bubbles when laminating color prints or pictures.

Speed and temperature are automatically controlled by semi-permanent infrared non-contact temperature sensor.

Easy operation : Pre-set key according to the type of operation

Safe operation : Cooling fan assures stable temperature for long-time operation

Power saving : Auto Stand-by (No operation over 90minutes)

Safety : Auto Shut-down (No operation over 2 hours in stand-by mode)

9 different jobs with one machine

1. Hot lamination
2. Cold lamination
3. Mounting upto 3mm
4. Micronex pouch overlay coating
5. Gloss and matt sleeking
6. Hologram sleeking
7. Metallic foil sleeking
8. Embossing lamination
9. Thermal transfer



Specification

| Model Name | FASTSYNC-320R6 | FASTSYNC-470R6 |
|-----------------------|-------------------------------------|-------------------------------------|
| Laminating Speed | 2830mm/min | 2830mm/min |
| Laminating Width | 320mm | 470mm |
| Laminating Films | 75mic~300mic | 75mic~300mic |
| Substrate Thickness | 80g/m ² ~ 2mm | 80g/m ² ~ 2mm |
| Thickness of Mount | 3mm | 3mm |
| Front Roller Diameter | 30/31mm | 30/31mm |
| Rear Roller Diameter | 30mm | 30mm |
| Power Requirements | 220~240V, 50/60Hz | 220~240V, 50/60Hz |
| Power Consumption | 1670W, 7.3A | 2570W, 10.75A |
| Warm up time | 3 minutes | 3 minutes |
| Heating System | Hot Roller Internal Infrared Heater | Hot Roller Internal Infrared Heater |
| Operating Temperature | 150°C Max | 150°C Max. |
| Clam shell open | Open | Open |
| Speed Control | Key Pad Number Direct | Key Pad Number Direct |
| Temperature Control | Key Pad temperature Direct | Key Pad temperature Direct |
| Cooling System | DC Fan | DC Fan |
| Dimensions(WxLxH) | 585 x 344 x 147mm | 745 x 344 x 147mm |
| Type of Main Motor | DC W-Geared Motor | DC W-Geared Motor |

※ GMP reserves the right to change specifications without prior notice.